

hitex-i

Innovative Hot Air Seam Sealing Machines
Only GoreTex machines are our competition!

HHC-3300 DDi

Delivery: 3-4 weeks

Hot Air Seam Sealing Machine

Sealing machine for normal seams with full electronic equipment for great technological flexibility and efficient production.

With the hitex-i hot air seam sealing machine You choose the innovation:
You can make your products in better quality and 10-20% faster.

We don't have options for our machines, we sell the complete machine with all features—
but we have unique solutions!

Heated upper roller, so it doesn't reduce the heat at the sealing, that's why You can make
better quality. We can keep the adjusted temperature in +/- 1 degrees.

Electronic tape dispenser for all our models, so the tape cannot stretch, because it can lead to worse quality and slower production.

Accurate tape cutting

Differential fabric feed with two direct drive motors for sealing hood and sleeve.

Training: We don't just sell the machine to our partners. **We teach them how to use the machine and if our partners have any questions about technology development, they can depend on us.**

Our references: We do the water proofing of firefighters, soldiers, policemen clothes and high quality sportswear since 2006. We have the experience, You can count on Us!



hitex-i

HEAD OFFICE and SHOWROOM:
HU-BUDAPEST
KÉSMÁRK STREET 11-13.
+361 410 4735
beo@beokft.hu



Innovative Hot Air Seam Sealing Machines
Only GoreTex machines are our competition!

CHARACTERISTICS

1. Upper&down proportional speed adjustment system (dual motor)
2. LCD Display panel
3. Slide Cam Style'S Nozzle Movement
4. Error message for heater problem
5. Emergency System for heather's over voltage
6. New design, soft movement's foot pedal
7. Upper/down roller's chain tension control system
8. Auto stop when goods are rolled up
9. Auto controller for tape tension
10. Nozzle angle controller
11. Auto cooling
12. Auto tape cutting system
13. Use of 2&3 layer
14. Forward/reverse rotation
15. Backlashing stop
16. Safety for nozzle cover
17. Feeding type cutter
18. Stop-mark free device
19. Light sensor for curing prevention system
20. Device for holding a margin to seam
21. Semeconductor light

SPECIFICATION

Power Requirement	Single/Triple Phase 220V +/- 10% 50/60Hz
Electric Consumption	1.5KVA
Compressed Air	2.2KW
Width of adhesive tape	10~23mm (Optional extra)
Upper roller lift	30mm/Optional extra
Speed	1~16M/min Digital read-out of operating speed
MAX Temperature	Up to 699 C
Heater Capacity	3600 W



HEAD OFFICE and SHOWROOM:
HU-BUDAPEST
KÉSMÁRK STREET 11-13.
+361 410 4735
beo@beokft.hu